


22432 DALLA CT-DTO50-B

Ceiling-mounted spotlight fitting















Kanlux DALLA is a very carefully made holder for installation inside. It has a movable ring, thanks to which you can adjust the light stream. Its shapes and universal colours allow achieving a modern, discrete effect of elegance.

GENERAL DATA:

Colour: black

Necessity of using self-shielding lamps: yes **Place of assembly**: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Replaceable light source: yes

The product is not suitable to be installed on a normally

flammable surface: >35W

The product is not suitable to be covered with a heat-

insulating material: yes Light source included: no

Height [mm]: 26 Diameter [mm]: 82

Assembly hole [mm]: Ø70 Wire length [m]: 0.12

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC Maximum power [W]: max 50

Class of protection against electric shock: III

Light source: MR16

Cap: Gx5,3

Ambient temperature range to which the product can be

exposed: 5÷25

The fixture is adapted to the light sources of the

following energy classes: A++,A+,A,B,C,D,E

Enclosure material: aluminum alloy Connection type: Free cable ends Wire diameter [mm²]: 0.75

Lighting-fixture angle regulation [°]: 30

IP class: 20





22432 DALLA CT-DT050-B

Ceiling-mounted spotlight fitting



