| 成品尺寸	75*75mm
展开图尺寸:	75*300mm
公差:	±1mm

单位:mm

Control Panel 8 Pro

Installation Manual

## Installation Notes ⚠

1. In order to ensure the correct use of this product, it must be installed, maintained and disassembled by a professional electrician.
2. Before installing and disassembling this product, the main power switch must be cut off to prevent electric shock.
3. This product should be kept away from fire and water sources during installation and use, and should not be used in humid environments (such as bathrooms).
4. Confirm that the voltage is in line with the working voltage of this product before use, and do not insert the PoE network cable into the network port.

5. Do not repair the product by yourself. Any modification or flashing of the product without authorization will void the warranty.
6. The product needs to be installed by technicians. The installation environment is concrete wall.
7. The distribution box must be plastic and non-hygroscopic material, with a minimum fire-resistance rating of 5V.
8. There should be no other metal conductive objects in the distribution box.
9. The distance between the opening of the product body and the opening of the junction box should be at least 1 cm.
10. The device does not support PoE power supply, so please do not plug the PoE cable into the network port to avoid damaging the device.

Installation Instructions

● Turn off the main power switch, and use a test pen to confirm that the live wire of the cassette is not charged.

● Remove the Panel and in-wall power base (below):

① Remove the screws at the bottom, and then remove the panel and the power supply base.

Installation Instructions

Wiring Instructions

| RJ45 | 485 R+R-+L- | | RJ45 | 485 R+R-+L- |

L-L+R-R+

Light line 2
Light line 1

Neutral wire   Live wire

Light line 1
Light line 2

Live wire   Neutral wire

Light line 1
Light line 2

Live wire   Neutral wire

US Spec
Power Base

European Spec
Power Base

Asian Spec
Power Base

● Please connect according to the actual marking on the product

L: Live wire input   RJ45：Wired Network port
N: Neutral wire input   485：485A&B
L1: Light line 1
L2: Light line 2   R-R+：Speaker
Stripping length 10mm   L-L+：Speaker

● Connect the base correctly, make sure that the copper wire and the terminal are well released, and there is no exposed wire.

Installation Instructions

wall

cassette

② Use mounting screws to fix the base into the concealed box.

Pay Attention

● Do not use force when installing the screws, so as not to cause deformation of the bracket.

③ Align the panel with the base bracket from top to bottom.
④ Close the panel and the base.
⑤ Attach the bottom screws to fix it.

版本	物料编号	变更者	变更时间	版本升级原因描述
1.0				原始版本

材质	105铜版纸	客户		产品名称	智慧中控屏8PRO	物料名称	智慧中控屏8PRO-中性-安装指南	设计	大川
印刷色	单黑	中性						审核	陈莉莉
加工工艺	风琴4折页,正反印刷			型号	TPA08-M3A&M3E&M3U	物料编号		时间	20241127
接合方式									