

VERTO BLOCK CCT

SLI003052CCT_PW

Façade luminaire VERTO BLOCK CCT with the possibility of changing the light color (CCT), with a power of 20 W, high light efficacy 120 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 2700 / 4000 / 6000K, we can adjust the light color depending on our needs and preferences. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. Designed for surface mounting.



Power	20 W	Voltage	230 V
Luminous flux*	2400 lm (360°)	Colour temperature	2700/4000/6000 K
Colour of light	CCT	Beam angle	160/120 °
Degree of protection (IP)	IP65		

Technical data

Logistics data

Code	SLI003052CCT_PW
Power	20 W
Nominal current	160 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.5
Useful luminous flux*	2400 lm (360°)
Luminous flux	1600 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	2700/4000/6000 K
Colour of light	CCT
Beam angle	160/120 °
RA	80
Light source included	+
Dimmable	No
Working temperature range	-20/+40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	Plastic
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	320x130x100 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC
Other	Light color change function 2700K/4000K/6000K ,

Bulk packaging	10 pcs.
Quantity per pallet	240 pcs.
Gross weight (1 pcs.)	0.85 kg

*applies to the LED source used

Related documents



User manual



Declaration of Conformity



Photometric file

