

# LIMEA GIGANT

SLI028026NW\_PW

Hermetic luminaire LIMEA GIGANT, with a power of 52 W, high light efficacy 171 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



|                 |                       |                           |               |
|-----------------|-----------------------|---------------------------|---------------|
| Power           | <b>52 W</b>           | Voltage                   | <b>230 V</b>  |
| Luminous flux*  | <b>8900 lm (360°)</b> | Colour temperature        | <b>4000 K</b> |
| Colour of light | <b>Neutral white</b>  | Beam angle                | <b>120 °</b>  |
| IK              | <b>10</b>             | Degree of protection (IP) | <b>IP65</b>   |

## Technical data


---

|                              |                           |
|------------------------------|---------------------------|
| Code                         | SLI028026NW_PW            |
| Power                        | 52 W                      |
| Nominal current              | 235 mA                    |
| Voltage                      | 230 V                     |
| Energy consumption           | 52 kWh/1000h              |
| Frequency                    | 50HZ Hz                   |
| Protection class             | I                         |
| Power supply included        | +                         |
| Power factor                 | 0.99                      |
| Useful luminous flux*        | 8900 lm (360°)            |
| Luminous flux**              | 8000 lm (360°)            |
| Lamp efficacy                | 171 lm/W                  |
| Luminous intensity           | 2500 cd                   |
| Colour temperature           | 4000 K                    |
| Colour of light              | Neutral white             |
| Beam angle                   | 120 °                     |
| RA                           | 80                        |
| Uniformity of color SDCM max | 3                         |
| Dimmable                     | No                        |
| Working temperature range    | -20/+40 °                 |
| Lifespan                     | 50000 h                   |
| Housing material             | POLYCARBONATE             |
| IK                           | 10                        |
| Degree of protection (IP)    | IP65                      |
| Colour                       | Gray/White                |
| Dimension (AxBxC)            | 1550x72x70 mm             |
| For use                      | Inside/Outside            |
| Assembly method              | On the ceiling, Suspended |
| Application                  | INT/EXT                   |
| Made in                      | PRC                       |
| Other                        | MAX 16 pcs per line ,     |

## Related documents

---



 User manual



 Declaration of Conformity



 Photometric file

---

