

NOCTIS LUX 4

SLI029068WW_PW

Floodlight NOCTIS LUX 4, with a power of 100 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with a warm light (3000K). Designed for surface mounting.

IP65

IK07



Power	100 W	Voltage	230 V
Luminous flux*	8700 lm (120°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	100 °
IK	07	Degree of protection (IP)	IP65

Technical data

Code	SLI029068WW_PW
Power	100 W
Nominal current	425 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	8700 lm (120°)
Luminous flux**	8700 lm (360°)
Lamp efficacy	87 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	251x207x26 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity

