

NYMPHEA FUSION CCT

SLI031056CCT_PW

Plafond NYMPHEA FUSION CCT with the possibility of changing the light color (CCT), with a power of 20w / 30w / 40w W, high light efficacy 135 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000 / 4000 / 6000K, we can adjust the light color depending on our needs and preferences. It has a high IP44 rating, making it ideal for use in rooms with high humidity. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	20W/30W/40W W	Voltage	230 V
Luminous flux*	5400 lm (360°)	Colour temperature	3000/4000/6000 K
Colour of light	CCT	Beam angle	120 °
Degree of protection (IP)	IP44		

Technical data

Code	SLI031056CCT_PW
Power	20W/30W/40W W
Nominal current	175 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.950000
Useful luminous flux*	5400 lm (360°)
Luminous flux	2300/3400/4500 lm (360°)
Lamp efficacy	135 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	Plastic
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	330x53 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	Light color change function 3000K/4000K/6000K ,

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	120 pcs.
Gross weight (1 pcs.)	0.88 kg

*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity



 Photometric file

