

ORBITO NATYNKOWA

SLI043039WW_PW

LED luminaire ORBITO NATYNKOWA, with power regulation on the power supply (14-27 W), high light efficacy 110 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 40° gives directional light so that selected objects or surfaces can be better exposed. Designed for surface mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	14-27 W
Colour temperature	3000 K
Beam angle	40 °
IK	06

Voltage	230 V
Colour of light	WW
UGR	<19
Degree of protection (IP)	IP44

Technical data

Code	SLI043039WW_PW
Power	14-27 W
Nominal current	125 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.900000
Useful luminous flux*	3000 lm (360°)
Luminous flux	1200-2300 lm (360°)
Lamp efficacy	110 lm/W
Luminous intensity	3300 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum
IK	06
Degree of protection (IP)	IP44
Colour	Black
Dimension (AxBxC)	115x152 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

Logistics data

Bulk packaging	18 pcs.
Quantity per pallet	270 pcs.
Gross weight (1 pcs.)	1.05 kg



*applies to the LED source used

Related documents

 User manual Declaration of Conformity Photometric file

