

# PLATEO SUN 3

SLI044031NW\_PW

PLATEO SUN 3 HIGH BAY 200W NW 230V 90DEG IP65 IK06 309X65MM BLACK

IP65

IK06



|                 |                        |                           |               |
|-----------------|------------------------|---------------------------|---------------|
| Power           | <b>200 W</b>           | Voltage                   | <b>230 V</b>  |
| Luminous flux*  | <b>22050 lm (360°)</b> | Colour temperature        | <b>4000 K</b> |
| Colour of light | <b>Neutral white</b>   | Beam angle                | <b>90 °</b>   |
| IK              | <b>06</b>              | Degree of protection (IP) | <b>IP65</b>   |

## Technical data

---

|                              |                 |
|------------------------------|-----------------|
| Code                         | SLI044031NW_PW  |
| Power                        | 200 W           |
| Nominal current              | 870 mA          |
| Voltage                      | 230 V           |
| Energy consumption           | 200 kWh/1000h   |
| Frequency                    | 50HZ Hz         |
| Protection class             | I               |
| Power factor                 | 0.9             |
| Useful luminous flux*        | 22050 lm (360°) |
| Luminous flux**              | 20000 lm (360°) |
| Lamp efficacy                | 110 lm/W        |
| Luminous intensity           | 8700 cd         |
| Colour temperature           | 4000 K          |
| Colour of light              | Neutral white   |
| Beam angle                   | 90 °            |
| RA                           | >80             |
| Uniformity of color SDCM max | 5               |
| Dimmable                     | No              |
| Working temperature range    | -20 to +40 °    |
| Lifespan                     | 17000 h         |
| Housing material             | Aluminum/PC     |
| IK                           | 06              |
| Degree of protection (IP)    | IP65            |
| Colour                       | Black           |
| Dimension (AxBxC)            | 309x68 mm       |
| For use                      | Outside         |
| Assembly method              | Suspended       |
| Application                  | Outside         |
| Made in                      | PRC             |

## Related documents

---



 Declaration of Conformity