

HALLS LINE 3

SLI048010NW_PW

HALLS LINE 3 HIGH BAY 75W NW 230V 60X90DEG IP66 IK10 440X130X115MM BLACK 5Y WARRANTY 1-10V



Power	75 W	Voltage	230 V
Luminous flux*	12375 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	60x90 °
IK	10	Degree of protection (IP)	IP66

Technical data

Code	SLI048010NW_PW
Power	75 W
Nominal current	350 mA
Voltage	230 V
Energy consumption	75 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.950000
Useful luminous flux*	12375 lm (360°)
Luminous flux	12000 lm (360°)
Lamp efficacy	165 lm/W
Luminous intensity	11300 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	60x90 °
RA	80
Light source included	Yes
Dimmable	Yes
Working temperature range	20 +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum
IK	10
Degree of protection (IP)	IP66
Colour	Czarny
Dimension (AxBxC)	440x130x115 mm
For use	Outside / Inside
Assembly method	Suspended
Whether it should work in conditions other than normal	Yes
Made in	PRC

Logistics data

Quantity per pallet	88 pcs.
Gross weight (1 pcs.)	2.9 kg

*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity



 Photometric file

