

# NOCTIS SOLARIS MINI

SLI050001

LED luminaire NOCTIS SOLARIS MINI, with a power of 2 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. It shines with a cold light (6000K). Designed for surface mounting.

IP65



Power **2 W**  
Colour temperature **6000 K**  
Beam angle **110 °**

Voltage **3.7 V**  
Colour of light **CW**  
Degree of protection (IP) **IP65**

## Technical data

|                              |                                                      |
|------------------------------|------------------------------------------------------|
| Code                         | SLI050001                                            |
| Power                        | 2 W                                                  |
| Voltage                      | 3.7 V                                                |
| Protection class             | III                                                  |
| Luminous flux**              | 200 lm (360°)                                        |
| Colour temperature           | 6000 K                                               |
| Colour of light              | CW                                                   |
| Beam angle                   | 110 °                                                |
| RA                           | 80                                                   |
| Uniformity of color SDCM max | 5                                                    |
| Dimmable                     | No                                                   |
| Working temperature range    | -20/+40 °                                            |
| Lifespan                     | 17000 h                                              |
| Housing material             | Plastic+Glass                                        |
| Degree of protection (IP)    | IP65                                                 |
| Colour                       | Black                                                |
| Dimension (AxBxC)            | 145x175x30 mm                                        |
| For use                      | Outside                                              |
| Assembly method              | On the ceiling                                       |
| Application                  | EXT                                                  |
| Made in                      | PRC                                                  |
| Other                        | Light sensor, PIR sensor,<br>Sensor distance: 3-5m , |



## Related documents



 User manual



 Declaration of Conformity

